



## MEDIA DISPLAY<sup>®</sup> MINI

EXTRAORDINARY PRESENTATION  
OF YOUR ADVERTISING MESSAGE

### DESIGN OBJECT AND ADVERTISING MESSAGE IN ONE DEVICE

TFT screens are integrated in a tower housing with CF card reader or optional hard disk drive and integrated speakers.

On the Spot, no PC or video is needed, just a power socket.

This device enables you to screen your commercials mobile, flexible and professionally in any indoor area. The relatively big tower surface can be used for individual artworks matching your Corporate ID and enhancing effectiveness of your advertising.

- ✦ **Datastorage on CF-Card**
- ✦ **2,5" HDD optional**
- ✦ **Housing in your CI-Design optional**
- ✦ **No PC or video needed**
- ✦ **Built-in speakers**



### CLIENTELE

Car Dealers and Car Rentals  
Drug Stores and Perfumeries  
Hair Dressers and Beauty Parlours  
Hotels and Restaurants  
Jewellers and Goldsmiths  
Pharmacy and Opticians  
Retail Trade and Discounter  
Stores and Outlets  
Travel Offices and Agencies

### APPLICATIONS

Beauty and Wellness  
Commercial and Photo Show  
Fashion and Lifestyle  
Health and Care  
Jewels and Accessories  
Pleasure and Cosiness

### LOCATIONS

Fairs and Corporate Events  
Permanent Exhibitions and Window Dressing  
Presentation of Wares and Products  
Promotion Tours and Product Launches  
Sales Promotion and Road Shows



## MEDIA DISPLAY<sup>®</sup> MINI

EXTRAORDINARY PRESENTATION  
 OF YOUR ADVERTISING MESSAGE

### TECHNICAL DATA

Scope of supply: ready-to-use in metal tower housing, with built-in CF-Card Reader, speakers and USB interface for data transfer. Including external Power Supply unit and Remote Control. Hard disc drive optional.

Stored files are replayed in auto loop function.

For installation, only a 230-V power socket is needed.

#### + GENERAL DATA

Model	✦ <b>WOS MD 6.5i</b>
Panel Size	✦ <b>6.5" (16 cm)</b>
Aspect Ratio	✦ <b>16:9</b>
Speakers	✦ <b>5W</b>
<b>GREEN IT</b> Power Consumption	✦ <b>~ 50 W</b>
Power Supply	✦ <b>100 - 240 VAC 50/60 Hz</b>
Input	✦ <b>USB 2.0 Type A and CF-Card Type II Slot</b>
Storage Device	✦ <b>CF-Card Typ I/II and 2.5" HDD (optional)</b>
Remote Control	✦ <b>Yes</b>
OSD	✦ <b>Yes</b>
Certificates	✦ <b>CE, FCC, UL, VCCI</b>
Environmental Temperature	✦ <b>0° C - 60° C</b>
Environmental Humidity	✦ <b>5% - 95%</b>
Dimensions (W x H x D) mm	✦ <b>210 x 460 x 55,7 mm</b>
Net Weight	✦ <b>4,9 kg</b>

#### + MONITOR

Max. Resolution	✦ <b>0.120 x0.339</b>
Color	✦ <b>480 x 234</b>
Contrast	✦ <b>256K</b>
Brightness	✦ <b>400:1</b>
Response Time (Tr/Tf) (ms)	✦ <b>450 cd/m<sub>2</sub></b>
View Angle	✦ <b>10 / 30</b>
Pixel Pitch	✦ <b>45° / 130°</b>
Backlight	✦ <b>1CCFL</b>